Digital Cabinets Refrigerated Counter 160 lt undercounter

ITEM #		
MODEL #		
NAME #		
SIS #		
ΔΙΔ #		



Digital Cabinets

Refrigerated Counter 160 lt undercounter

727030 (RUCR16X1) Undercounter Refrigerator 160

It - 1 door / stainless steel -230 V/1N/50Hz

727046 (RUCR16W1) Undercounter Refrigerator 160

lt - 1 door / white - 230

V/1N/50Hz

Short Form Specification

Item No.

The Electrolux range of 160 liter refrigerated counters offers customers a reliable, compact and easy to use cold storage. All the internal finishings are in commercial grade High Impact Polystyrene and all models require only 1 phase 220/240 V supply, allowing to be plugged directly into an existing power socket. Models are designed to operate at an ambient temperature of up to 43°C. The models detailed in this sheet are 160 liter undercounter refrigerators with stainless steel or white painted door.

Main Features

- Internal light and lockable door.
- R134a gas in refrigeration circuit.
- Suitable for use in ambient temperatures of up to 43 °C.
- Refrigerators models have operating temperatures that can be adjusted from +2 to +10 $^{\circ}\text{C}$ to suit both meat and dairy storage requirements.
- Very quiet operation: noise level less than 45 dB (A).
- Automatic defrost and automatic evaporation of defrost
- Shelf runners are thermoformed and are incorporated in the internal structure to be easily cleanable.
- Compact cooling unit easily accesible from the rear of the appliance.
- Model requires only 1 phase 220/240V supply and can be plugged straight into an existing power socket.
- Temperature display.

Construction

- Interior cell is completely in white High Impact Polystyrene and has no joints to eliminate dirt traps.
- CFC and HCFC-free insulation.
- Refrigerant type: R134a.
- IP23 protection index.
- Developed and produced in ISO 9001 and ISO 14001 certified factory.
- Built-in compressor.
- The rounded internal corners, the easily removable grids allow for ease of cleaning and high hygiene standards.
- 30 mm thick insulation with cyclopentane injection for longterm insulation and energy saving.
- Reversible door.

Optional Accessories

Door covering kit for 160lt for


	undercounter refrigerators (cover panel not included)	
•	Stacking kit for 160lt undercounter refrigerator, prepainted grey (only for 727030)	PNC 880146
•	Wall hanging kit for 160lt undercounter refrigerator	PNC 880149
•	Set of 3 grids for 160lt undercounter refrigerator, prepainted grey (only for 727030)	PNC 880151
•	Bottle holder for 3 bottles, 160lt	PNC 880159


APPROV	AL:
---------------	-----

PNC 880145




Digital Cabinets Refrigerated Counter 160 It undercounter





EI = Electrical connection



Electric

Supply voltage:

727030(RUCR16X1) 230 V/1 ph/50 Hz **727046(RUCR16W1)** 230 V/1 ph/50 Hz **Connected load:** 0.17 kW

Key Information:

Door hinges:Right SideExternal dimensions, Height:850 mmExternal dimensions, Width:600 mm

External dimensions, Depth with

Doors Open:0 mmNumber and type of doors:1 FullGross capacity:165 ltNoise level:45 dBAHeight adjustment:0/10 mm

Number and type of grids

(included): 3 -Built-in Compressor and Refrigeration Unit

Refrigeration Data

Control type: Mechanical

Compressor power:

Refrigerant type: R134a **Refrigeration power:** 153 W

Refrigeration power at

evaporation temperature: -12 °C

Refrigerant weight: 65 g

Operating temperature min.: 2 °C

Operating temperature max.: 10 °C

External side panels:

727030(RUCR16X1) Prepainted Steel **727046(RUCR16W1)** Prepainted white

External top panels:

727030(RUCR16X1) Grey ABS **727046(RUCR16W1)** White ABS

External door material:

Side

727030(RUCR16X1) Stainless Steel **727046(RUCR16W1)** Prepainted white

Internal panels material: High Impact White Polystyrene

Operating mode: Ventilated







